

# Avery Weigh-Tronix

## Portable Truck Scales


**BridgeMont** BMS-P

**BridgeMont** BMS DT-P

**SteelBridge** IMXT-P



*Fully-enclosed sandwich steel construction for greater strength and corrosion protection.*



*Modular sections bolt together at the installation site.*

**Avery Weigh-Tronix portable scales go anywhere there is an immediate need for on-site truck weighing — mining and timber operations, road construction, asphalt facilities, quarries or construction sites. They can also quickly step-in to fill the gap when other scales fail.**

**Focus on productivity with same-day setup and operation.**



*Installs on any stable surface — fast assembly and leveling.*

Avery Weigh-Tronix Portable Truck Scales can be installed in just 2–4 hours on any stable surface, including: bridge planks, concrete piers or blocks, a concrete slab or swamp pad. The self-contained modular sections eliminate costly site preparation. Each section incorporates built-in Weigh Bar® weight sensors, leveling pads and dedicated conduit runs for fast setup and disassembly.

## Features and benefits

**Durability for the long haul** — Nowhere is structural integrity more critical than in a portable truck scale. The ability to provide accurate measurement under extreme environmental conditions, frequent moves and heavy loading requires exceptional strength and engineering. Avery Weigh-Tronix Portable scales meet the challenge with sandwich steel construction: a checkered steel deck, supported by full-length structural steel members and stabilized with a complete bottom plate. A continuous perimeter weld seals the entire assembly against moisture and premature corrosion.

**Proven Weigh Bar® reliability** — In a three-year study on 250 truck scales, the Weigh Bar exhibited an annual failure rate of just 0.75% – compared with an industry average of 3 to 5% for load cells.

To add to the overall reliability, Weigh Bar cable is sheathed in stainless steel and internally routed for superior protection against moisture, wear and rodents.

**Permanent installation** — When a temporary need turns into a long-term application, there's no need to purchase a new scale. All models of the BMS-P, BMS DT-P and IMXT-P can be readily converted to permanent, low-profile truck scales.

## Specifications

	BMS-P	BMS DT-P	IMXT-P
Dual Tandem Axle Rating	70,000 lb	80,000 lb	90,000 lb
Concentrated Load Capacity (CLC)	35 tons	40 tons	45 tons
"r" Factor Rating	2.06	2.35	2.65
Weight Sensors: Weigh Bars	60K	60K	60K
Top Plate: Checkered	1/4"	1/4"	3/8"

**Height:** 19 inches

**Finish:** Sandblasted steel components with epoxy primer and alkyd top coat

**Junction Boxes:** Stainless steel NEMA 4X

**Surge Voltage Protection:** Standard

**Cable:** Stainless steel sheathed Weigh Bar cable and 50' interface cable

### Bulkheads:

- 13' structural "C" channel type bulkheads (one pair) included with 10' wide models
- 14' structural "C" channel type bulkheads (one pair) included with 11' wide models

**Operating Environment:** -30° to 130° F

**Approvals:** NTEP, CC#97-074 (BMS and BMS DT) and CC#98-040 (IMXT)

### BMS-P 70,000lb DTA/35 ton CLC, 10' wide, 19" profile

Model	Capacity(lb)	Length	Modules	Ship Wt(lb)
BMS-P 2010	80,000	20'	1	10,906
BMS-P 2410	80,000	24'	1	11,950
BMS-P 4010	160,000	40'	2	19,190
BMS-P 4710	160,000	47'	2	21,277
BMS-P 6010	200,000	60'	3	27,493
BMS-P 7010	200,000	70'	3	30,623
BMS-P 7510	200,000	75'	3	32,188
BMS-P 8010	200,000	80'	4	35,777
BMS-P 9310	200,000	93'	4	39,949
BMS-P 10010	200,000	100'	4	42,036

### BMS DT-P 80,000lb DTA /40 ton CLC, 11' wide, 19" profile

Model	Capacity(lb)	Length	Modules	Ship Wt(lb)
BMS DT-P 2411	90,000	24'	1	13,332
BMS DT-P 4711	180,000	47'	2	23,898
BMS DT-P 7011	200,000	70'	3	34,391
BMS DT-P 9311	200,000	93'	4	45,049

### IMXT-P 90,000lb DTA/45 ton CLC, 10' wide, 19" profile

Model	Capacity(lb)	Length	Modules	Ship Wt(lb)
IMXT-P 2010	100,000	20'	1	12,492
IMXT-P 2410	100,000	24'	1	13,769
IMXT-P 4010	200,000	40'	2	22,238
IMXT-P 4710	200,000	47'	2	24,791
IMXT-P 6010	200,000	60'	3	32,005
IMXT-P 7010	200,000	70'	3	35,833
IMXT-P 8010	200,000	80'	4	41,751
IMXT-P 9310	200,000	93'	4	46,856
IMXT-P 10010	200,000	100'	5	51,527

## Options

Battery operated or AC powered instrumentation

Welded guide rails

Guide posts

Custom lengths and widths available

Remote Displays

## Avery Weigh-Tronix

Fairmont, Minnesota U.S.A.  
 USA Toll-Free: 800-368-2039  
 USA Phone: 507-238-4461  
 www.wtxweb.com

Pointe Claire, Quebec Canada  
 CAN Toll-Free: 800-561-9461  
 CAN Phone: 514-695-0380  
 www.weigh-tronix.ca

